

06-15-00

A



PATENT APPLICATION  
Attorney Docket No. 5038-46  
Client Ref. No. P8744

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

EXPRESS MAIL

MAILING LABEL NO. EL 432977796 US  
DATE OF DEPOSIT: JUNE 13, 2000

I HEREBY CERTIFY THAT THIS PAPER AND ENCLOSURES AND/OR FEE ARE BEING DEPOSITED WITH THE UNITED STATES POSTAL SERVICE "EXPRESS MAIL POST OFFICE TO ADDRESSEE" SERVICE UNDER 37 CFR 1.10 ON THE DATE INDICATED ABOVE AND IS ADDRESSED TO: BOX PATENT APPLICATION, ASSISTANT COMMISSIONER FOR PATENTS, WASHINGTON D.C. 20231.

MELISSA C. SMITH  
(SENDER'S PRINTED NAME)

*Melissa C. Smith*  
(SIGNATURE)

JCS844 U.S. PTO

09/593922



## Box Patent Application

Assistant Commissioner for Patents  
Washington, DC 20231

Enclosed for filing is a patent application under 37 CFR 1.53(b) of:

Inventor: Robert A. Jacobs

For: METHOD AND APPARATUS FOR SELECTING INTERNET-BASED  
BROADCAST SOURCES

## Enclosures:

[X] Specification (pages 1-5); claims (pages 6-7); abstract (page 8)

[X] 2 sheets of drawings

[X] Declaration or Combined Declaration and Power of Attorney

[X] Assignment with cover sheet

CLAIMS AS FILED				
For	Number Filed	Number Extra	Rate	Basic Fee \$690.00
Total Claims	17-20	0	x \$ 18 =	
Independent Claims	3-3	0	x \$ 78 =	
TOTAL FILING FEE				\$690.00

METHOD AND APPARATUS FOR SELECTING INTERNET-BASED BROADCAST SOURCES


[X] A check in the amount of \$730.00 to cover [X] filing fee and the [X] assignment recordal fee (\$40) is enclosed.

[X] Any deficiency or overpayment should be charged or credited to deposit account number 13-1703. A duplicate copy of this sheet is enclosed.

Customer No. 20575

Respectfully submitted,

MARGER JOHNSON  
& McCOLLOM, P.C.

  
Julie L. Reed  
Reg. No. 35,349

MARGER JOHNSON & McCOLLOM, P.C.  
1030 S.W. Morrison Street  
Portland, OR 97205  
(503) 222-3613

Figure 1 displays 12 histograms showing the distribution of the number of non-zero elements in the vector  $x$  for different values of  $n$  (10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120). The x-axis is labeled 'x' and ranges from 0 to 120. The y-axis is labeled 'count' and ranges from 0 to 100. As  $n$  increases, the distribution of  $x$  becomes more concentrated around zero, with the peak count increasing significantly.

Figure 1 displays 12 histograms showing the distribution of the number of non-zero elements in the vector  $x$  for different values of  $n$  (10, 20, 30, 40, 50, 60, 70, 80, 90, 100, 110, 120). The x-axis is labeled 'x' and ranges from 0 to 120. The y-axis is labeled 'count' and ranges from 0 to 100. As  $n$  increases, the distribution of  $x$  becomes more concentrated around zero, with the peak count increasing significantly.

**METHOD AND APPARATUS FOR SELECTING  
INTERNET-BASED BROADCAST SOURCES**

**BACKGROUND**

1. Field

This disclosure relates to control of Internet-based, broadcast source reception, and more particularly to a method and apparatus that allows quick selection of these radio stations.

2. Background

Numerous Internet-based broadcast sources have come into existence recently. Additionally, numerous broadcast radio stations have begun to provide substantially simultaneous broadcast over the Internet. These broadcast sources may be referred to as Internet radio stations, even though they do not use radio waves to broadcast across the Internet. Currently, users may listen to these stations over the sound system in their personal computers, using one of several audio players. Examples of these audio players include Real Player™ software from RealNetworks, Inc. and Microsoft Windows® MediaPlayer™ software from Microsoft Corporation. These particular players, as well as others, have versions that may be freely downloaded from the companies' sites.

In addition to the player software, lists of available broadcast stations may be easily accessed from the Internet. Some companies that provide player software also provide lists of stations. Others are independent of the players, but have links to the various players from their sites.

To use these players, the user typically accesses the Internet and locates a station to which he or she wants to listen. The user selects the link and the appropriate player launches and buffers the audio stream. This process may take up to two minutes, depending upon the system and connection speeds, employing typical state-of-the-art technology.

If an interruption occurs, the user repeats this process. This may or may not involve re-launching the browser. However, the user typically selects another link and waits while the player buffers up the next selection. This problem hinders Internet broadcasts from having wider user acceptance, including acceptance of Internet "radio" products.

## BRIEF DESCRIPTION OF THE DRAWINGS

The invention may be best understood by reading the disclosure with reference to the following drawings, wherein:

Figure 1 shows a block diagram of an embodiment of an apparatus for Internet radio reception in accordance with the invention.

Figure 2 shows a flow chart of an embodiment of a process of operating an Internet radio receiver in accordance with the invention.

Figure 3 illustrates an embodiment of an Internet radio receiver including a stream selector in accordance with the invention.

## DETAILED DESCRIPTION

Internet broadcast sources have become more prevalent recently, a trend that will likely continue. The term Internet radio sources include those that are transmitted only over the Internet as well as those that are available over the Internet and by traditional broadcasts. Similarly, the term Internet is used because it easily identifies the current worldwide network of computers that communicates using a defined protocol. As used in this discussion, the term Internet will also apply to any network of computer or computing platforms capable of utilizing email and/or a browser.

One embodiment of an apparatus operable to receive and deliver Internet radio sources to a user is shown in Figure 1. This apparatus, shown by the dashed box, will be referred to as a stream manager. The Internet radio sources, as defined above, are received by the apparatus across the Internet. The sources are then routed to their own respective stream receiver, 12a, 12b ... 12n. A stream receiver maintains a connection with one of the multiple Internet radio sources.

The mechanics of maintaining the connection may be done in several ways. One embodiment of the stream manager apparatus of Figure 1 is best implemented as multi-threaded software. Multi-threaded software as used here is software that can do several things at once. The software operates to identify the data received from the Internet as belonging to one of the radio stations and then routing that data through the thread for that station. It performs this routing for each of the identified stations. However, the invention is not limited to one particular approach.

Corresponding stream buffers 14a, 14b ... 14n store the respective streams. The stream buffers operate as 'bit buckets,' storing the last interval of the stream of data from the

receiver for that source. The interval would typically be a time interval such as, for example, the previous  $x$  seconds of the transmission. This allows stream selector 16 to change sources without the typical pause in the transmissions that occurs in current audio players used for Internet radio.

5           The memory used for the stream buffers may be implemented in several ways and the invention is not limited in scope to a particular approach. For example, in a current personal computer comprising a central processing unit and storage devices, such as hard disk drives and random access memory (RAM), the buffers may be implemented as segments of the RAM. The software may direct the processor to store and retrieve the appropriate stream  
10   from the appropriate section of the RAM. In one implementation of memory for the stream buffers, however, the buffers allow the stream selector to present the selected source to the user with little, if any, perceptible pause in audio output signal.

          The streams to be buffered may be identified in several ways and the invention is not limited in scope to a particular approach. Preferably, the user may designate several  
15   “favorites” and these may be buffered to reduce or avoid delays in transmission. Alternatively, the user may designate a radio format, or some other characteristic that will allow identification of the streams to be buffered.

          The stream selector 16 operates to select which of the buffered streams will be presented to the user as audio output signals 18. The stream selector may make the selection  
20   based on a predefined list of user preferences, as mentioned above, in which the stations are prioritized. The prioritization may be based upon user preferences prioritized depending upon the time of day, as an example. Alternatively, the stream selector may employ present user input information. For example, the user may listen to one of the stations and desire to change to another station because of a commercial, the start of an unwanted program or other  
25   reason. The user may designate another selected station and the stream selector would operate select the appropriate stream.

          In this embodiment of multi-threaded software, the software may identify the selected source from user input information. The software may then identify which thread and corresponding buffer is receiving and storing the data for that source. The software may then  
30   route the data for that source to the system output port or channel.

          An embodiment of a method of operation in accordance with the invention is shown in Figure 2. At 20, the streams are identified, as discussed above, and buffered at 22. The selection of the stream to be output is made at 24 and that stream is presented to the user at

26. If an interruption occurs, such as from user input information, a loss in transmission, or a loss of connection, as examples, the process returns to 22 or 24, via paths 28 or 30, respectively. In this embodiment, the process would just return to the selection at 24 and the interrupted stream becomes a buffered stream that is not selected as the audio output signal.

5 However, it is possible that the user input could be selection of a new source that is not one of the sources already buffered, returning the process to 22.

In this last example, the advantage of quickly switching stations would be lost on the initial identification of a new source, but would be recovered upon subsequent switches involving that station. It is noted that the number of stations identified may be limited only  
10 by the system non-volatile memory capacity and the speed of the processor in executing the instructions of the software.

The processor and memory for implementing the stream manager may be contained in any one of a number of system configurations. As an example, a personal computer has been discussed above. In addition, a dedicated apparatus such as an Internet radio receiver may  
15 implement the stream manager. Such an apparatus may be considered analogous to a typical personal radio or a 'boom box' currently available today. For ease of discussion, and with no intent to limit application of the invention, this embodiment will be referred to as an Internet radio receiver. An example of such a receiver is shown in Figure 3.

In this embodiment, radio receiver 40 receives data from the Internet radio sources at  
20 42. The Internet port 42 could be a cable, such as a modem or network cable, or a wireless connection. The data is then handled by the interface 44 in this embodiment. The interface may depend upon the type of Internet connection used. In the case of a modem cable, the interface comprises a modem. In the case of a network cable, the interface comprises a network interface, such as an Ethernet card. If the connection is wireless, the connection  
25 comprises a wireless receiver and the interface comprises a wireless modem, such as a Bluetooth™ adapter or other manager for wireless connection. If the connection is a power-line data connection, the interface would be a power-line data interface

The receiver in this embodiment includes the stream manager 15, which includes the stream selector 16. The selected one of the Internet radio sources would be provided as audio  
30 output signals from the stream selector, as indicated by 46a and 46b. These would in turn provide audio output signals to the user by speakers 50a and 50b. In addition, a representation of the selected Internet radio source may be displayed on the display 48, such

as a liquid crystal display. Two speakers are shown here, but one speaker, or more than two, depending upon the user's preference, may be employed in alternative embodiments.

If the stream manager were implemented on a personal computer, similar functionality could be provided to the user. In either case, as well as any other example, the computing  
5 device upon which the stream manager executes is able to access and read the computer readable media containing the program code. The program code allows the apparatus to receive and deliver Internet radio sources to a user according to the processes and methods set forth above.

Thus, although there has been described to this point a particular embodiment for a  
10 method and structure for an Internet radio stream manager, it is not intended that such specific references be considered as limitations upon the scope of this invention except in-so-far as set forth in the following claims.



## WHAT IS CLAIMED IS:

- 1 1. A method to change audio sources broadcast over a network, the method comprising:  
2 separately buffering multiple audio sources transmitted across the network so as to  
3 reduce delay when audio sources are changed.
- 1 2. The method of claim 1, the method further comprising selecting one of the multiple audio  
2 sources using a stream selector.
- 1 3. The method of claim 1, the method further comprising routing each of the multiple audio  
2 sources to a stream receiver operable to maintain connection with that audio source.
- 1 4. The method of claim 3, the method further comprising delivering the selected one of the  
2 multiple audio sources as audio output signals to a user.
- 1 5. The method of claim 1 wherein buffering of the multiple audio sources is accomplished  
2 by one of the group comprised of: a computer having browsing software, and an Internet  
3 radio receiver.
- 1 6. The method of claim 1 wherein selecting one of the multiple audio sources is  
2 accomplished with one of the group comprised of: predefined user inputs, and a present  
3 user input.
- 1 7. An Internet radio receiver operable to switch between multiple audio sources and deliver  
2 radio receiver output to a user, the receiver comprising:  
3 a stream manager operable to receive and buffer the multiple Internet radio sources  
4 and to select one of the multiple Internet radio sources.
- 1 8. The receiver of claim 7 wherein the receiver further comprises a connector operable to  
2 receive the multiple audio sources.
- 1 9. The receiver of claim 8, wherein the connector is one of a group comprised of: a modem  
2 cable, a wireless receiver, a power line, and a network cable.

1 10. The receiver of claim 8 wherein the receiver further comprises an interface between the  
2 connector and the stream manager.

1 11. The receiver of claim 10, wherein the interface is one of a group comprised of: a modem,  
2 a network interface card, a power line data interface and a wireless modem.

1 12. The receiver of claim 7 further comprising at least one speaker operable to present the one  
2 of the multiple audio sources to a user as audio output signals.

1 13. The receiver of claim 7 further comprising a display operable to display an identifier of a  
2 selected one of the multiple audio sources.

1 14. The receiver of claim 7 wherein the stream manager further comprises:

- 2 a) multiple stream receivers each operable to receive one of the multiple audio sources;
- 3 b) corresponding stream buffers each operable to receive data from one of the multiple  
4 stream receivers;
- 5 c) a stream selector operable to select one of the multiple audio sources as output to a  
6 user.

1 15. An article comprising:

- 2 a) a storage medium, the storage medium having stored thereon instructions, that, when  
3 executed by a computing device, result in:
  - 4 i) reception of multiple audio sources using a stream receiver for the multiple audio  
5 sources;
  - 6 ii) buffering of the multiple audio sources received from the stream receivers; and
  - 7 iii) selection of one of the multiple audio sources and to produce audio output signals.

1 16. The article of claim 14 wherein said computing device comprises a personal computer.

17. The article of claim 14 wherein said computing device comprises an Internet radio  
receiver having a processor.

# METHOD AND APPARATUS FOR QUICKLY SELECTING INTERNET-BASED RADIO STATIONS

## ABSTRACT

5           A method and apparatus to quickly change and deliver Internet radio sources. The apparatus can receive multiple Internet radio sources simultaneously, and route each of the multiple Internet radio sources to a stream receiver. The stream receiver is operable to maintain connection with one of a multitude of Internet radio sources. Each of the sources can be buffered by a stream buffer that can receive data from one of each of the stream  
10 receivers. A stream selector can select one of the multiple Internet radio sources and deliver the selected one of the multiple Internet radio sources as output to a user. The apparatus can be implemented as part of a multiple function system such as a personal computer or as an Internet radio receiver apparatus.

15



COMBINED DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION

As a below named inventor(s), I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention which

- ☒ is attached hereto.  
☐ was filed on \_\_\_\_\_ as Application No. \_\_\_\_\_  
☐ and was amended on \_\_\_\_\_ (if applicable)  
☐ with amendments through \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, Sec. 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Sec. 119 (a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			Claiming Priority?	
			<input type="checkbox"/>	<input type="checkbox"/>
(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
_____	_____	_____		

I hereby claim the benefit under Title 35, United States Code, Sec. 119(e) of any United States provisional application listed below:

Provisional Application No.

Filing Date

I hereby claim the benefit under Title 35, United States Code, Sec. 120 or §365(c) of any PCT international application designating the United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Sec. 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Sec. 1.56 which

METHOD AND APPARATUS FOR SELECTING INTERNET-BASED BROADCAST SOURCES

occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application No.) (Filing Date) (Status) (patented, pending, abandoned)

I hereby appoint the following attorneys to prosecute the application, to file a corresponding international application, to prosecute and transact all business in the Patent and Trademark Office connected therewith:

Customer No. 20575

<u>Attorney Name</u>	<u>Registration No.</u>
Jerome S. Marger	26,480
Alexander C. Johnson, Jr.	29,396
Alan T. McCollom	28,881
James G. Stewart	32,496
Glenn C. Brown	34,555
Stephen S. Ford	35,139
Julie L. Reed	35,349
Gregory T. Kavounas	37,862
Scott A. Schaffer	38,610
Joseph S. Makuch	39,286
James E. Harris	40,013
Graciela G. Cowger	42,444
Ariel Rogson	43,054
Craig R. Rogers	43,888

Direct all telephone calls to Julie L. Reed at (503) 222-3613 and send all correspondence to:

MARGER JOHNSON & MCCOLLOM, P.C.  
1030 S.W. Morrison Street  
Portland, Oregon 97205

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: Robert A. Jacobs

Inventor's signature:

Robert A. Jacobs

June 1, 2000  
(Date)

Residence: Portland, Oregon

Citizenship: USA

Post Office address: 2515 N.E. 40<sup>th</sup> Ave., Portland, OR 97212

METHOD AND APPARATUS FOR SELECTING INTERNET-BASED BROADCAST SOURCES